



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- -type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*2216*01

Reason for extension: Technical modifications

SECTION I

0.1. Make (trade name of manufacturer) : Bosal

0.2. Type and general commercial description(s) : 027051

0.3. Means of identification of type marked on the

component

0.3.1. Location of that marking : On type plate

0.5. Name and address of manufacturer : Bosal Le Rapide Rue de Reims

F-51490 Beine Nauroy France

0.7. In the case of components and separate technical: On type plate

units, location and method of

affixing of the EEC type approval mark

0.8. Address(es) of assembly plant(s) : See information document

(annex III, item 0.8)

Type approval number

Type-approval number: e4*94/20*2216*01

SECTION II

1. Additional information (where applicable) See Appendix I

Technical service responsible for carrying out

RDW

the tests Testbaan|Centrum

> Talingweg 76 8218 NX Lelystad

02-09-2004 Date of test report

28-02-2005

4. Number of test report RDW-94/20-3955

RDW-94/20-3083

Remarks (if any) See Appendix I 5.

6. Place Zoetermeer

28-02-2005 7. Date

8. Signature

2.

3.

J.P.M. Laumen

- The index to the information package lodged with the competent authority that has granted 9. type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*2216*01 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1. Additional information

1.1. Class of the type of coupling

A50-X

1.2. Categories or types of vehicles for which

the device is designed or restricted

See fitting instructions

1.3. Maximum D-value

9,10

kN

1.4. Maximum vertical load S at the coupling point:

70

kg

1.5 Maximum load U at the fifth wheel

ton

coupling point

kN

1.6. Maximum V-value

1.7.

Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles See fitting instructions



1.8 Information on the fitting of special towing

brackets or mounting plates

See fitting instructions

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.