

Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

febi 172009 antifreeze Ready Mix G12+ (-35°C) Article number: 172009, 172010, 172011

UFI: PRCC-5GPN-V00E-SQF6

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Anti-freezing agents

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

Company +49 2333 911-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Acute Tox. 4: H302 Harmful if swallowed.

STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure if

swallowed. (kidneys)

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms



Signal word WARNING

Contains: Ethylene glycol

Hazard statements H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

(kidneys)

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P260 Do not breathe vapours / spray.

P270 Do no eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell.

P314 Get medical advice / attention if you feel unwell.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.





Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022 Version 03. Supersedes version: 02

Page 2 / 12

2.3 Other hazards

Human health dangers It is essential for pregnant women to avoid inhaling the product and not to let it come in

contact with the skin.

Environmental hazards Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 **Substances**

not applicable

3.2 **Mixtures**

The product is a mixture.

Range [%]	Substance
40 - 50	Ethylene glycol
	CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
	GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373
< 3	Sodium 2-ethylhexanoate
	CAS: 19766-89-3, EINECS/ELINCS: 243-283-8
	GHS/CLP: Repr. 2: H361d

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

Description of first aid measures

General information Change soaked clothing.

Inhalation Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Do not induce vomiting.

Most important symptoms and effects, both acute and delayed 4.2

Tiredness Unconsciousness Headache Vertigo

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 **Extinguishing media**

Suitable extinguishing media Carbon dioxide.

Water spray jet. Dry powder. Foam.

Extinguishing media that must not

be used

Full water jet.

Safety Data Sheet (UK REACH) (GB)

febi 172009 antifreeze Ready Mix G12+ (-35°C) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 3 / 12

5.2 Special hazards arising from the substance or mixture

risk of formation of toxic pyrolysis products, carbon monoxide (CO), not combusted hydrocarbons

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provide solvent-resistant and impermeable floor.

Use solvent-resistant equipment. Use only in well-ventilated areas.

Keep away from all sources of ignition - Refrain from smoking.

Take precautionary measures against static discharges.

Vapours can form an explosive mixture with air.

Remove soiled or soaked clothing immediately.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Do not store together with oxidizing agents.

Do not store with alkalies.

Do not store together with food and animal food/diet.

Protect from heat/overheating and from sun.

Keep container in a well-ventilated place.

Keep container tightly closed.

Recommended storage temperature: < 40°C

7.3 Specific end use(s)

See product use, SECTION 1.2



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 4 / 12

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Ethylene glycol

CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX

Long-term exposure: 20 ppm, 52 mg/m³, Vapour, particulate: 10 mg/m³

Short-term exposure (15-minute): 40 ppm, 104 mg/m³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES

Ethylene glycol

CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX

Eight hours: 20 ppm, 52 mg/m³, H

Short-term (15-minute): 40 ppm, 104 mg/m³

DNEL

_		
С.	ıbstance	_

Sodium 2-ethylhexanoate, CAS: 19766-89-3

Industrial, dermal, Long-term - systemic effects, 2 mg/kg bw/day

Industrial, inhalative, Long-term - systemic effects, 14 mg/m³

general population, oral, Long-term - systemic effects, 1 mg/kg bw/day

general population, dermal, Long-term - systemic effects, 1 mg/kg bw/day

general population, inhalative, Long-term - systemic effects, 3.5 mg/m³

Ethylene glycol, CAS: 107-21-1

Industrial, dermal, Long-term - systemic effects, 106 mg/m³

Industrial, inhalative, Long-term - local effects, 35 mg/m³

general population, dermal, Long-term - systemic effects, 53 mg/m³

general population, inhalative, Long-term - local effects, 7 mg/m³

PNEC

Substance

Sodium 2-ethylhexanoate, CAS: 19766-89-3

soil, 57.9 µg/kg soil dw

sediment (seawater), 30.1 µg/kg sediment dw

sediment (freshwater), 301 µg/kg sediment dw

sewage treatment plants (STP), 71.7 mg/L

seawater, 36 µg/L

freshwater, 360 µg/L

Ethylene glycol, CAS: 107-21-1

freshwater, 10 mg/L

seawater, 1 mg/L

sediment (freshwater), 37 mg/kg

soil, 1,53 mg/kg

sewage treatment plants (STP), 199,5 mg/l (AF=10)

sediment (seawater), 3,7 mg/kg



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 5 / 12

8.2 Exposure controls

Additional advice on system design Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance

requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

The details concerned are recommendations. Please contact the glove supplier for further Hand protection

information.

0,45 mm Nitrile rubber, >480 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

It is essential for pregnant women to avoid inhaling the product and not to let it come in

contact with the skin.

Respiratory protection Respiratory protection mask in the event of high concentrations.

Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)

Thermal hazards

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state liauid Color Purple

Odor characteristic

Odour threshold No information available.

pH-value 7,5 - 11

pH-value [1%] not determined

Boiling point [°C] >107

Flash point [°C] No information available.

Flammability (solid, gas) [°C] not applicable Lower explosion limit not applicable Upper explosion limit not applicable

Oxidising properties nο

Vapour pressure/gas pressure [kPa] 0,123 hPA (25°C)

Density [g/cm³] 1,05 - 1,07 Relative density not determined Bulk density [kg/m³] not applicable Solubility in water miscible

No information available. Solubility other solvents Partition coefficient [n-octanol/water] No information available. Kinematic viscosity No information available. Relative vapour density No information available. **Evaporation speed** No information available.

Melting point [°C] -35 **Auto-ignition temperature** 440

Decomposition temperature [°C] No information available. Particle characteristics No information available.



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 6 / 12

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents. Reactions with acids.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 7 / 12

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Product	
ATE-mix, oral, > 300 mg/kg bw	

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
LD50, oral, Rat, 2043 mg/kg bw, OECD 401

Ethylene glycol, CAS: 107-21-1

LD50, oral, Rat, 7712 mg/kg bw

ATE, oral, 500 mg/kg (Acute Tox. 4)

Acute dermal toxicity

Substance	
Sodium 2-ethylhexanoate, CAS: 19766-89-3	
LD50, dermal, Rat, 2000 mg/kg bw, OECD 402, 24h	
Ethylene glycol, CAS: 107-21-1	
LD50, dermal, mouse, >3500 mg/kg bw	

Acute inhalational toxicity

Substance	
Sodium 2-ethylhexanoate, CAS: 19766-89-3	
LC0, inhalative, Rat, 0.11 mg/L air, OECD 403, 8h	
Ethylene glycol, CAS: 107-21-1	
LC50, inhalative, Rat, >2.5 mg/L air, 6h	

Serious eve damage/irritation	Based on available data, the classification criteria are not met

Substance	
Ethylene glycol, CAS: 107-21-1	
Eye, non-irritating	

Skin corrosion/irritation	Based on available data, the classification criteria are not met.

Substance	
Ethylene glycol, CAS: 107-21-1	
dermal, non-irritating	

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Substance	
Ethylene glycol, CAS: 107-21-1	
dermal, non-sensitizing	

Specific target organ toxicity — single exposure	Based on available data, the classification criteria are not met.
Specific target organ toxicity — repeated exposure	May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys) Calculation method

Substance
Ethylene glycol, CAS: 107-21-1



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 8 / 12

NOAEL, dermal, Dog, 2200 mg/kg bw/day, adverse effect observed

NOEL, oral, Rat, 150 mg/kg bw/day, OECD 408, adverse effect observed

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance

Ethylene glycol, CAS: 107-21-1

in vitro, no adverse effect observed

Reproduction toxicity (CAS: 19766-89-3): This product contains one or more substances of categorie Repr. 2 (CLP).

Based on the available information, the classification criteria are not fulfilled.

Calculation method

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on available data, the classification criteria are not met.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

11.2 Information on other hazards

Endocrine disrupting properties No information available.

Other information none

SECTION 12: Ecological information

12.1 Toxicity

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
LC50, (96h), Oryzias latipes, >100 mg/l (OECD 203)
EC50, (72h), Desmodesmus subspicatus, 49,3 mg/l
NOEC, (21d), Daphnia magna, 25 mg/l (OECD 211)
EC0, (48h), Daphnia magna, 62,5 mg/l (Directive 79/831/EEC, Annex V, Part C)
Ethylene glycol, CAS: 107-21-1
LC50, (28d), fish, 1,5 g/L
LC50, (3d), fish, 72.86 g/L
EC50, (4d), Invertebrates, 3,536 - 13 g/L
EC50, (21d), Invertebrates, 33,911 g/L
EC50, (48h), Invertebrates, 100 mg/L

12.2 Persistence and degradability

Behaviour in environment

not determined

compartments

Behaviour in sewage plant not determined

Biological degradability The product is biodegradable.

12.3 Bioaccumulative potential

Product has having no bioaccumulation potential.

12.4 Mobility in soil

No information available.



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 9 / 12

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

160114*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

not applicable

IMDG

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Inland navigation (ADN)

Transport by land according to

NO DANGEROUS GOODS

ADR/RID

NO DANGEROUS GOODS

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

IMDG

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

Safety Data Sheet (UK REACH) (GB)

febi 172009 antifreeze Ready Mix G12+ (-35°C) Article number 172009, 172010, 172011



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 10 / 12

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

no

Inland navigation (ADN)

Marine transport in accordance with no

IMDG

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2022)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

0 %

- Observe employment restrictions

for people

Observe employment restrictions for young people.

Observe employment restrictions for mothers-to-be and nursing mothers.

Observe employment restrictions for women of child-bearing age.

- VOC (2010/75/CE)



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 11 / 12

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H302 Harmful if swallowed.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

Route

RID = Règlement concernant le transport international ferroviaire de marchandises

dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par

voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration

ECB = European Chemicals Bureau EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure Acute Tox. 4: H302 Harmful if swallowed. (Calculation method)

STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure if

swallowed. (kidneys) (Calculation method)

Modified position none



Ferdinand Bilstein GmbH + Co. KG

Date printed 02.03.2022, Revision 02.03.2022

Version 03. Supersedes version: 02

Page 12 / 12