

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SWAG 33 10 1130 antifreeze Ready Mix G13 (-35°C)
Article number: 33 10 1130, 33 10 1131, 33 10 1132
UFI: H8DC-6GU1-Q00D-RRXK

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Anti-freezing agents

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

1.3 Details of the supplier of the safety data sheet

Company SWAG Autoteile GmbH
Am Kiesberg 4-6
42117 Wuppertal / GERMANY
Phone +49 (0)202 26454-0
Fax +49 (0)202 26454-5000
Homepage www.swag.de
E-mail info@swag.de

Address enquiries to

Technical information info@swag.de

Safety Data Sheet info@swag.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Acute Tox. 4: H302 Harmful if swallowed.
STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys)

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms



Signal word

WARNING

Contains:

Ethylene glycol

Hazard statements

H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys)

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe vapours / spray.
P270 Do not eat, drink or smoke when using this product.
P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor if you feel unwell.
P314 Get medical advice / attention if you feel unwell.
P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards

Human health dangers	It is essential for pregnant women to avoid inhaling the product and not to let it come in contact with the skin.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
40 - 50	Ethylene glycol CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX GHS/CLP: Acute Tox. 4: H302 - STOT RE 2: H373
< 3	Sodium 2-ethylhexanoate CAS: 19766-89-3, EINECS/ELINCS: 243-283-8 GHS/CLP: Repr. 2: H361d

Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%. For full text of H-statements: see SECTION 16.
----------------------------	---

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Change soaked clothing.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
Eye contact	In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.
Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Tiredness
Unconsciousness
Headache
Vertigo

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to your doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide. Water spray jet. Dry powder. Foam.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

risk of formation of toxic pyrolysis products, carbon monoxide (CO), not combusted hydrocarbons

5.3 Advice for firefighters

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous earth).

Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provide solvent-resistant and impermeable floor.

Use solvent-resistant equipment.

Use only in well-ventilated areas.

Keep away from all sources of ignition - Refrain from smoking.

Take precautionary measures against static discharges.

Vapours can form an explosive mixture with air.

Remove soiled or soaked clothing immediately.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and after work.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Do not store together with oxidizing agents.

Do not store with alkalies.

Do not store together with food and animal food/diet.

Protect from heat/overheating and from sun.

Keep container in a well-ventilated place.

Keep container tightly closed.

Recommended storage temperature: < 40°C

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Ethylene glycol
CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
Long-term exposure: 20 ppm, 52 mg/m ³ , Vapour, particulate: 10 mg/m ³
Short-term exposure (15-minute): 40 ppm, 104 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
Ethylene glycol
CAS: 107-21-1, EINECS/ELINCS: 203-473-3, EU-INDEX: 603-027-00-1, Reg-No.: 01-2119456816-28-XXXX
Eight hours: 20 ppm, 52 mg/m ³ , H
Short-term (15-minute): 40 ppm, 104 mg/m ³

DNEL

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
Industrial, dermal, Long-term - systemic effects, 2 mg/kg bw/day
Industrial, inhalative, Long-term - systemic effects, 14 mg/m ³
general population, oral, Long-term - systemic effects, 1 mg/kg bw/day
general population, dermal, Long-term - systemic effects, 1 mg/kg bw/day
general population, inhalative, Long-term - systemic effects, 3.5 mg/m ³
Ethylene glycol, CAS: 107-21-1
Industrial, dermal, Long-term - systemic effects, 106 mg/m ³
Industrial, inhalative, Long-term - local effects, 35 mg/m ³
general population, dermal, Long-term - systemic effects, 53 mg/m ³
general population, inhalative, Long-term - local effects, 7 mg/m ³

PNEC

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
soil, 57.9 µg/kg soil dw
sediment (seawater), 30.1 µg/kg sediment dw
sediment (freshwater), 301 µg/kg sediment dw
sewage treatment plants (STP), 71.7 mg/L
seawater, 36 µg/L
freshwater, 360 µg/L
Ethylene glycol, CAS: 107-21-1
freshwater, 10 mg/L
seawater, 1 mg/L
sediment (freshwater), 37 mg/kg
soil, 1,53 mg/kg
sewage treatment plants (STP), 199,5 mg/l (AF=10)
sediment (seawater), 3,7 mg/kg

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. 0,45 mm Nitrile rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Light protective clothing.
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin. It is essential for pregnant women to avoid inhaling the product and not to let it come in contact with the skin.
Respiratory protection	Respiratory protection mask in the event of high concentrations. Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	Purple
Odor	characteristic
Odour threshold	No information available.
pH-value	7,5 - 11
pH-value [1%]	not determined
Boiling point [°C]	>107
Flash point [°C]	No information available.
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	not applicable
Upper explosion limit	not applicable
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	0,123 hPa (25°C)
Density [g/cm³]	1,05 - 1,07
Relative density	not determined
Bulk density [kg/m³]	not applicable
Solubility in water	miscible
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	No information available.
Kinematic viscosity	No information available.
Relative vapour density	No information available.
Evaporation speed	No information available.
Melting point [°C]	-35
Auto-ignition temperature	440
Decomposition temperature [°C]	No information available.
Particle characteristics	No information available.

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

Reactions with acids.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
LD50, oral, Rat, 2043 mg/kg bw, OECD 401
Ethylene glycol, CAS: 107-21-1
LD50, oral, Rat, 7712 mg/kg bw
ATE, oral, 500 mg/kg (Acute Tox. 4)

Acute dermal toxicity

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
LD50, dermal, Rat, 2000 mg/kg bw, OECD 402, 24h
Ethylene glycol, CAS: 107-21-1
LD50, dermal, mouse, >3500 mg/kg bw

Acute inhalational toxicity

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
LC0, inhalative, Rat, 0.11 mg/L air, OECD 403, 8h
Ethylene glycol, CAS: 107-21-1
LC50, inhalative, Rat, >2.5 mg/L air, 6h

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Substance
Ethylene glycol, CAS: 107-21-1
Eye, non-irritating

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Substance
Ethylene glycol, CAS: 107-21-1
dermal, non-irritating

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Substance
Ethylene glycol, CAS: 107-21-1
dermal, non-sensitizing

Specific target organ toxicity — single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity — repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys)
Calculation method

Substance
Ethylene glycol, CAS: 107-21-1
NOAEL, dermal, Dog, 2200 mg/kg bw/day, adverse effect observed
NOEL, oral, Rat, 150 mg/kg bw/day, OECD 408, adverse effect observed

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Substance
Ethylene glycol, CAS: 107-21-1
in vitro, no adverse effect observed

Reproduction toxicity (CAS: 19766-89-3): This product contains one or more substances of categorie Repr. 2 (CLP).
Based on the available information, the classification criteria are not fulfilled.
Calculation method

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard Based on available data, the classification criteria are not met.

General remarks

Toxicological data of complete product are not available.
The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

11.2 Information on other hazards

Endocrine disrupting properties No information available.

Other information none

SECTION 12: Ecological information

12.1 Toxicity

Substance
Sodium 2-ethylhexanoate, CAS: 19766-89-3
LC50, (96h), Oryzias latipes, >100 mg/l (OECD 203)
EC50, (72h), Desmodesmus subspicatus, 49,3 mg/l
NOEC, (21d), Daphnia magna, 25 mg/l (OECD 211)
EC0, (48h), Daphnia magna, 62,5 mg/l (Directive 79/831/EEC, Annex V, Part C)
Ethylene glycol, CAS: 107-21-1
LC50, (28d), fish, 1,5 g/L
LC50, (3d), fish, 72.86 g/L
EC50, (4d), Invertebrates, 3,536 - 13 g/L
EC50, (21d), Invertebrates, 33,911 g/L
EC50, (48h), Invertebrates, 100 mg/L

12.2 Persistence and degradability

Behaviour in environment compartments not determined

Behaviour in sewage plant not determined

Biological degradability The product is biodegradable.

12.3 Bioaccumulative potential

Product has having no bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended)

160114*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Waste no. (recommended)

150110* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Transport by land according to ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with IMDG

not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

Marine transport in accordance with IMDG

NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EC 2000/532/EC; 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2022)
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK REACH; GB CLP.
- Observe employment restrictions for people	Observe employment restrictions for young people. Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for women of child-bearing age.
- VOC (2010/75/CE)	0 %

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H302 Harmful if swallowed.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Acute Tox. 4: H302 Harmful if swallowed. (Calculation method)
STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys) (Calculation method)

Modified position

none

Safety Data Sheet (UK REACH) (GB)

SWAG 33 10 1130 antifreeze Ready Mix G13 (-35°C)

Article number 33 10 1130, 33 10 1131, 33 10 1132

SWAG Autoteile GmbH

42117 Wuppertal

Date printed 03.03.2022, Revision 03.03.2022



Version 03. Supersedes version: 02

Page 12 / 12